

P. C. B LAYOUT

Electrical Specification:
 Rated Voltage: 250V AV.DC
 Rated Current: 3A
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstand voltage: 1500V AC/Min
 Temperature range for usage: -25°C~+85°C

Material:
 Housing: PA9T UL94V-0
 Contacts: Brass/Gold-flash

PART NO.	Dimensions (mm)	
	A	B
02P	2.54	8.53
03P	5.08	11.07
04P	7.62	13.61
05P	10.16	16.15
06P	12.70	18.69
07P	15.24	21.23
08P	17.78	23.77
09P	20.32	26.31
10P	22.86	28.85
11P	25.40	31.39
12P	27.94	33.93

General description of ordering code


FAMILY	ROWS	N° POLES	VERSION	CLIP PLATING	PEG
GM254	1	XX	N [smt right angle]	F [flash gold]	W [with peg]
				T [tin]	O [without]



euro-conn



UNITS: mm		SHEET SIZE: ISO A4		SCALE: ---	
> 0 ~ 3	> 3 ~ 18	> 18 ~ 50	> 50 ~ 120		
± 0.12	± 0.15	± 0.3	± 0.5		



INTERCO254