

MATERIAL


Insulator: LCP Rated UL94V-0
Contacts: Phosphor Bronze
Shell: Phosphor Bronze
Pin Plated: Gold 3u" over 50u" nickel

ELECTRICAL

Current Rating: 1.0 Amps Max.
Contact Resistance: 30 mΩ Max
Insulation Resistance: 1000 MΩ Min
Dielectric Withstanding Voltage: 500 VAC / Minute

MECHANICAL

Mating force: 3.0Kg Max. (29. 4N)
Unmating force: 0. 5Kg Min (4. 9N)
Contact Retention: 0.3 Kg / Pin Min. (2.94N)
Operating Temperature: -55°C ~ +105°C



General description of ordering code

FAMILY	MODEL	CONTACTS	VERSION	CLIP PLATING	TYPE	COLOR	PACKAGE
USB	-	5	N [smt right angle]	F [flash gold]	D	N[black]	R [reel]
				G [gold 15u]			



euro-conn



UNITS: mm

SHEET SIZE: ISO A4

SCALE: ----

> 0 ~ 3
± 0.12

> 3 ~ 18
± 0.15

> 18 ~ 50
± 0.3

> 50 ~ 120
± 0.5

! I prodotti e le caratteristiche possono cambiare senza preavviso.
The products and their features may change without notice.

USB_MINI