



MATERIAL

- 1. HOUSING MATERIAL : PBT/PA46 UL94V-0.
- 2. CONTACT MATERIAL : PHOSPHOR BRONZE \varnothing 0.46mm.
- 3. PLATING : GOLD PLATING \varnothing 50u" OVER NICKEL.
- 4. SHIELD : 0.20mm THICKNESS COPPER ALLOY WITH NICKEL PLATED.

ELECTRICAL

- 1. VOLTAGE RATING : 125 VAC RMS.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500V DC .
- 5. DIELECTRIC DIELECTRIC RESISTANCE : 1000V AC RMS 50Hz. 1MIN.

MECHANICAL

- 1. DURRABILITY : 750 CYCLES MIN.
- 2. PCB RETENTIONPRE-SOLDER : 1 LB MIN.

ENVIRONMENTAL:

- 1. STORAGE : -40°C ~ +85°C.
- 2. OPERATION : -40°C ~ +85°C.

General description of ordering code

FAMILY	POSITIONS	CONTACTS	VERSION	TYPE	CLIP PLATING	FRONT-SHIELD
MJS	-	8	D [straight]	G [short]	F [flash gold]	N [without]
					S [gold 6u]	W [with]
					G [gold 15u]	



euro-conn



UNITS: mm

SHEET SIZE: ISO A4

SCALE: ----

> 0 ~ 3

> 3 ~ 18

> 18 ~ 50

> 50 ~ 120

± 0.12

± 0.15

± 0.3

± 0.5

! I prodotti e le caratteristiche possono cambiare senza preavviso.
The products and their features may change without notice.

MODULAR